4T-MOTO 20W50

(JASO MA, API SL)

- Our 4T-MOTO 20W50 is a multi-grade lubricant for use in 4-stroke motorcycle engines and is made from a premium blend of (Group II) base oils, plus a performance additive package.
- It is stable, eliminating viscosity breakdown providing a steady operation throughout the oils life.
- It offers protection during RPM increase to provide optimal engine performance and offers corrosion protection for critical engine parts.
- Contains detergents and dispersants to reduce buildups in the motor.
- Offers protection against wear and extends oil change intervals.
- Exceeds specification requirements of Japanese (JASO) MA and API SL.
- Available in 55Gall, 12/1Qts.

Typical Inspections	Method	Typical Results
Appearance	Visual	Brillant
Color	Visual	Amber
Specific Gravity @ 15.6°C	ASTM D-1298	0.881
Viscosity Index	ASTM D-2270	125
Pour Point °C (°F)	ASTM D-97	-18 (-0.4)
Flash Point C.O.C. °C (°F)	ASTM D-92	210 (410)
Fire Point C.O.C. °C (°F)	ASTM D-92	216 (420.8)
Viscosity @ 40°C, cSt	ASTM D-445	165.1
Viscosity @ 100°C, cSt	ASTM D-445	18.5

Meets/Exceeds Specifications

- API SL
-JASO MA
-SAE 20W50

gxoil.org

Product Code: GX.86.2050 **Revised:** 01/2020

Note: The general description, recommended uses, application data and statements in the product literature are guidelines. Because the product may be used for a variety of applications, over which GXOil & Grease, LLC has no control. GXOil & Grease, LLC assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at http://www.gxoil.org/

MADE IN USA